

3M™ Premium Liquid Wax
06005/60-4400-9512-7 (Quart)
06006/60-4400-9513-5 (Gallon)
06008/60-4400-9514-3 (50 Gallon)

- Clear coat safe
- Produces a high gloss and luster

WARNING! COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL. MAY CAUSE EYE AND SKIN IRRITATION.

Read carefully other cautions on the side/back panel.

WARNING! Combustible liquid and vapor. Vapor harmful. May cause eye, skin, nose and throat irritation and may affect the central nervous system causing dizziness, headache or nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Contains a chemical which can cause cancer.

Applications:

Designed for use by hand or with an orbital buffer for cleaning and polishing new car paint finishes. May also be used on non-oxidized used car paint finishes. Not recommended for use on vinyl tops, metalized plastic trim, flat black painted surfaces, decals or simulated wood panels.

To minimize the possibility of staining, do not apply in direct sunlight or onto a hot surface.

Directions for Use:

Hand:

1. Wash car and dry.
2. Apply wax to a clean, soft, dry terry cloth towel and spread uniformly over a panel size area (one door or fender, 1/2 hood or roof) using a firm circular motion. Allow to dry to a haze.
3. Buff to a high gloss using a clean, soft, dry terry cloth towel.

Random Orbital Buffer:

1. Wash car and dry.
2. Apply wax to the paint finish. Work a panel size area using an orbital buffer with a clean terry cloth bonnet, until a thin uniform film is achieved. Allow to dry to a haze.
3. Buff to a high gloss by hand using a clean, soft, dry terry cloth towel, or with the orbital buffer using a clean dry terry cloth bonnet.

PROTECT FROM FREEZING

Contains: Water (7732-18-5); Hydrotreated Light Petroleum Distillates(64742-47-8); Polishing Compound (1132-58-7); Stoddard Solvent (8052-41-3); Poly-Dimethylsiloxane (63148-62-9); Glycerin (56-81-5); 2-Butoxyethanol (111-76-2); Formaldehyde (50-00-0).

VOC REGULATED MATERIAL: VOC equal to or less than 15%. Consult state and local regulations.

Precautions: Keep away from heat and flame. Avoid eye and skin contact. Wash thoroughly after handling. Avoid breathing vapors. Use only with adequate ventilation. Do not ingest. Close container after each use.

KEEP OUT OF REACH OF CHILDREN.

Suggested First Aid: Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. **Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention. **Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention. **If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Additional Product Safety and Health Information Source:

Material Safety Data Sheet (MSDS 19-7327-0)

3M Automotive Aftermarket Division

3M Center/Bldg. 223-6N-01

St. Paul, MN 55144-1000

1-877-MMM-CARS (666-2277) or 651-737-6501

“3M” is a trademark of 3M Company.

© 3M 2004

Made in U.S.A.