




DIMENSIONS (Inches)

	XS	S	M	L	XL	XXL
A	8.7	9.0	9.4	9.8	10.2	10.6
B	3.4	3.6	3.8	3.9	4.1	4.3

SPECIFICATIONS

LINER MATERIALS	Gray Basetek Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit



PACKAGING

	XS	S	M	L	XL	XXL
CASE SIZE						
PER CARTON	144	144	144	144	144	144
CASE WEIGHT	19.40/lbs	20.28/lbs	21.38/lbs	23.36/lbs	24.25/lbs	26.01/lbs
CUFF COLOR						
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4542	EN Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

FEATURES

LINER

13g, Gray Basetek Liner

COATING

Gray Polyurethane Palm Coating

BENEFITS:

ANSI Cut Level A3
EN388 Cut Level 5
Improved Grip and Abrasion Resistance
Repels Liquids From Palm of Hand

CATEGORY:

Excel

APPLICATIONS:

Aerospace
Appliance Manufacturing
Automotive Assembly
HVAC/Sheet Metal
Metal Fabrication
Parts Assembly
Pulling Electrical Wires

Armor Guys reference number : 02-013

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)