

PRODUCT DATA SHEET



Product Description

An aluminum complex premium grade USDA H1 grease for use in food production and processing industries. This NLGI Grade 2 multi-purpose lubricant is white in color and

has a smooth buttery texture.

Applications

Anywhere lubrication is needed where it may come in contact with food, bottling machinery, breweries, canneries, carton/packaging equipment, dairies, food processing & handling equipment, meat processing plants, seamers at high speeds & pressure,

Unit Package Description

400 Pound Drum

Brand

Sta-Lube

Generic Description 1

Multi-purpose Food Grade Grease

Net Fill

400 Lb

UPC Code

072213356090

Unit Dimensions

35H x 23W x 23D in

Units Per Case

i Case

35H x 23W x 23D in

Case Dimensions Cases Per Pallet

435 lbs

Case Weight
I 2 of 5 Code

30072213356091

Appearance

White Semi-Solid to Solid Grease

Base Type

Aluminum Complex

Flashpoint

430°F

CPSC Flammability Class

None

Specific Gravity

0.89 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

40 Lbs

Plastic Safe

Not Determined

Evaporation Rate

<1 (butyl acetate=1)

Working Temp

-30 to 300°F

Last revised: 7/15/2015

Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com





PRODUCT DATA SHEET

5



4 Ball EP 500 Kg Weld
4 Ball Wear 0.6 mm typical

Drop Point 500°F

Oil Separation Not Determined

Oxidation Stability 5
Pour Point 0°F
I SO Viscosity Grade 68

Worked Penetration 265 to 295

Water Washout

Propellant None NSF Category Code H1

NSF Number 132939

DOT Proper Shipping Name Not Regulated

 VOC % (Federal)
 0.3

 VOC g/L (Federal)
 2.67

 VOC Lbs./Gal. (Federal)
 0.022

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 7/15/2015

Page 2 of 2

