

PRODUCT DATA SHEET

Thread Lubricant, 2 Wt Oz No. SL35924 | Item# 1007953 | Case# 1007952

Product Description A general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion. Safe for

use on ferrous and non-ferrous metals.

Applications For use on aluminum conduit, bolts, bushings, fittings,

flanges, nuts, pipes, plugs and screws.

Unit Package Description 2 Ounce Tube

Brand Sta-Lube

Generic Description 1 Thread Lubricant

Net Fill 2 Wt Oz

UPC Code 072213359244

Unit Dimensions 5.25H x 2.25W x 1.5D in

Units Per Case 50

Case Dimensions 8.75H x 11.75W x 13D in

Cases Per Pallet 36 Case Weight 9 lbs

I 2 of 5 Code 30072213359245

Amber Semi-Solid to Solid Grease **Appearance**

Lithium-12 Base Type

334°F Flash point (F) Flash point (C) 168°C Flammability Class - CPSC None

Spec Gravity Concentrate 0.90

Plastic Safe Not Determined

Film Type Grease

Evaporation Rate Very Slow

ISO Viscosity Grade 150 **NLGI** Grade


Working Temp (F) -20 to 250°F

Working Temp (C) -17.8 to 148.9°C

Last revised: 3/22/2018

Page 1 of 2







CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified





PRODUCT DATA SHEET



None

DOT Proper Shipping Name

Not Regulated

VOC % (Consumer Product

< 0.1

def)

VOC g/L (Consumer

< 0.9

Product def)

VOC lbs/gal (Consumer

< 0.01

Prod def)
VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.

Last revised: 3/22/2018 Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.