SL3150 -- Super White™ Multi-Purpose Lithium Grease, 14 Wt Oz



Product Description

A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.

Product Specifications

Applications Assembly lubes, bearings, break-in lubrication for

bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door

tracks, roller bearings, sleeve bearings.

Unit Package Description 14 Ounce Cartridge

Brand Sta-Lube

Generic Description 1 Super White Multi-Purpose Grease

 Net Fill
 14 Wt Oz

 UPC Code
 072213315004

Unit Dimensions 9.31H x 2.13W x 2.13D in

Units Per Case 10

Case Dimensions 9.5H x 4.5W x 11.38D in

Cases Per Pallet 150
Case Weight 11 lbs

I 2 of 5 Code 30072213315005

Appearance White Semi-Solid to Solid Grease

OdorFaint PetroleumBase TypeLithium-12Flashpoint475°FFlammabilityNon-flammable

Specific Gravity 0.9 at 60°F NLGI Grade 1.5
Timken OK Load [Lbs.] 25 Lbs

Plastic Safe Not Determined

Evaporation Rate <0.01 (Butyl Acetate=1)

Working Temp 0 to 300°F
4 Ball EP Not Determined
4 Ball Wear 0.6 mm (max)
Drop Point 350°F

LeakageNot DeterminedLow Temp TorqueNot Determined

Oil Separation 5 **Oxidation Stability** 10 **Pour Point** 0°F **ISO Viscosity Grade** 165 **Water Washout** <15% Worked Penetration 285 to 295 **Propellant** None **NSF Registered** No

DOT Proper Shipping Name Not Regulated

 VOC % (Federal)
 <0.1</td>

 VOC g/L (Federal)
 <0.9</td>

 VOC Lbs./Gal. (Federal)
 <0.01</td>

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.