

PIG® Stat-Mat® Absorbent Pad

MAT214 Heavyweight, 15" x 20", 100 pads



Clean up spilled fuels and solvents with the only pads proven to dissipate static.

- The best mat you can buy to reduce the risk of electrostatic discharge; a critical precaution around flammable liquids and vapors
- Stat-Mat Pads and Rolls pass NFPA 99 standards for static decay and surface resistivity, making them perfect for fueling areas and solvent cleanup
- Absorbs and retains oils and fuels - including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels - but not water
- Lasts 2X longer than ordinary mats for fewer change-outs; Eight layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind liquids or fiber residue
- Packaged in special static-dissipative bags to help reduce static charge buildup
- Floats to clean up spills on water
- Flame-resistant material won't burn immediately like cellulose mats; melts when exposed to high heat while on the job
- White color tells you it's only for oils and fuels
- Pads are ideal for catching drips and soaking up spills
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Heavy-weight construction is highly durable and absorbent for demanding tasks and large-volume cleanups



Specifications

Fluid Absorbed	Fuels; Oil-Based Liquids - Not Water
Special Feature	Anti-Static
Color	White
Dimensions	15" W x 20" L

Absorbency	Up to 22 gal. per bag
Absorbency per	Up to 28.16 oz. per pad
Mat Weight/Absorbency Level	Heavyweight
Perforated	Perforated Down Center Widthwise
Sold as	100 pads per bag
Weight	17 lbs.
NSN (National Stock Number)	4235-01-308-5150
# per Pallet	30
Composition	Polypropylene
UNSPSC	47131901
UV Resistant	No
Pigalog® Page Number	Page 53

Metric Equivalent

Absorbency per	Up to 832.7 mL per pad
Absorbency	Up to 83.3 L per bag
Dimensions	38.1cm W x 50.8cm L
Weight	7.7 kg

Technical Information

Certifications, Approvals and Ratings

NFPA 99, NFPA 77

Technical Documents

PIG® Oil-Only Absorbents

29 CFR 1910.106(h)(7)(i)(a)

29 CFR 1910.22(a)(2)

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com