



SPECIFICATION SHEET

9100-52758



33 cal/cm² ARC/FR TWILL COVERALL

- Arc Rating: ATPV 33 cal/cm²
- PPE 3 (HRC 3)
- Aramid high tenacity thread
- Bartacked at all stress points
- Protective stand up collar
- Storm guard with front hook and loop closure
- Side elasticized waist
- Aramid rib knit cuffs
- 2 waist side access pockets

STANDARDS MET

- NFPA 70E 2012
- ASTM F1506
- OSHA 29 CFR 1910

APPLICATIONS

- Electrical & Utilities
- Petrochemical
- Mining
- Gas
- Oil
- Military
- Welding
- Emergency Services

CARE INSTRUCTIONS

Machine wash warm, 165° F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

TECHNICAL DATA

| | |
|--------------|--|
| MATERIAL | 88% Cotton / 12% Nylon |
| CONSTRUCTION | Two layers, 9 oz FR Cotton over 9 oz FR Cotton |
| COLOR | ■ Navy |
| SIZES | S - 5X |
| PACKAGING | 10 per case |
| CASE WEIGHT | 2lbs per unit |
| COO | Mexico |

BARCODES

| ITEM | EACH | BOX | CASE |
|-----------------|------|-----|------|
| ■ 9100-52758/S | | | |
| ■ 9100-52758/M | | | |
| ■ 9100-52758/L | | | |
| ■ 9100-52758/XL | | | |
| ■ 9100-52758/2X | | | |
| ■ 9100-52758/3X | | | |
| ■ 9100-52758/4X | | | |
| ■ 9100-52758/5X | | | |
| ■ 9100-52758/6X | | | |



DIMENSIONS (in)

| | S | M | L | XL | 2X | 3X | 4X | 5X |
|----------|-------|-------|-------|-------|-------|-------|-------|-------|
| A | 36-38 | 40-42 | 44-46 | 48-50 | 52-54 | 56-58 | 60-62 | 64-66 |
| B | 32-34 | 36-38 | 40-42 | 44-46 | 48-50 | 52-54 | 56-58 | 60-62 |
| C | 34.5 | 35.5 | 36.5 | 38 | 39.5 | 41 | 42.5 | 44 |
| D | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 |

