



# SPECIFICATION SHEET

## 9100-75001



### 75 CAL/CM<sup>2</sup> - FLAME RESISTANT OVERALLS

- ARC Rating: ATPV 75 cal/cm<sup>2</sup>
- PPE 4 (HRC 4)
- Aramid high tenacity thread
- Bar-tacked at all stress points
- No metal pieces on garment
- Hook and loop adjustment at sides and bottom ankle cuffs
- Pass through pockets
- Covered zipper fly closure
- Elasticized waist

### STANDARDS MET

- NFPA 70E-2012
- ASTM F1506-10a
- ASTM F2178-12
- OSHA 29 CFR 1910.269

### APPLICATIONS

- Electrical & Utilities

### CARE INSTRUCTIONS

Machine wash warm, 165° F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

### TECHNICAL DATA

MATERIAL	Westex Ultrasoft 88% Cotton 12% High Tenacity Nylon
CONSTRUCTION	Multi Layers: 2 layers of 12 oz FR Cotton over 2 layers of 5.5 oz FR Cotton
COLOR	■ Navy
SIZES	S - 5X
PACKAGING	1/polybag
CASE SIZE	12" x 12" x 6" / 30.5cm x 30.5cm x 15.25cm
CASE WEIGHT	4 lbs / 1.8 kg
COO	USA

### BARCODES

ITEM	BAG	BOX	CASE
■ 9100-75001/S			
■ 9100-75001/M			
■ 9100-75001/L			
■ 9100-75001/XL			
■ 9100-75001/2X			
■ 9100-75001/3X			
■ 9100-75001/4X			
■ 9100-75001/5X			



### DIMENSIONS (in)

	M	L	XL	2X
<b>A</b>	36-38	40-42	44-46	48-50
<b>B</b>	32	32	32	32

