

Cut-off wheels

Flat (type 1) – Universal line PSF

Steel
Hardness grade P



General purpose wheels provide fast cutting performance and good service life. Recommended for universal cutting applications on steel.

Abrasive: Aluminum oxide A

Workpiece material

Steel

Applications

Cutting of sheet metal, sections and solid materials

Recommendations for use

- .040", .045" thickness for fast, convenient cutting with minimized burr formation.
- .040" cut-off wheels are highly recommended for cordless angle grinders due to their narrow kerf, their superior cutting characteristics and optimal handling. They deliver more cuts per battery charge, making them very economical.

PFERDERGONOMICS®




PFERDEFFICIENCY®



PFERD specification number

A 46/60 P PSF

| Diameter x thickness nominal [Inches] | Thickness metric [mm] | Bore [Inches] | EDP number |  | Max. RPM |
|---------------------------------------|-----------------------|---------------|------------|---|----------|
| Flat (type 1) | | | | | |
| 4 x .040 | 1.0 | 5/8 | 69940 | 25 | 15,300 |
| 4 x .045 | 1.6 | 5/8 | 69944 | 25 | 15,300 |
| 4-1/2 x .040 | 1.0 | 7/8 | 69945 | 25 | 13,300 |
| 4-1/2 x .045 | 1.6 | 7/8 | 69949 | 25 | 13,300 |
| 5 x .040 | 1.0 | 7/8 | 69950 | 25 | 12,200 |
| 5 x .045 | 1.6 | 7/8 | 69954 | 25 | 12,200 |
| 6 x .040 | 1.0 | 7/8 | 69960 | 25 | 10,200 |
| 6 x .045 | 1.6 | 7/8 | 69964 | 25 | 10,200 |

