

HANDSAFE XP

P708KFA



Benefits

- Extreme cut protection: TDM F
- CUT XP 15 Gauge: fine knitting for more comfort
- · Glove without glass fiber or stainless steel
- Contact heat resistant
- Touch Screen glove

BONUS

Nitrile reinforcement between thumb and index finger for improved durability.

Description

- Designed with high performance fibers without glass fibers or stainless steel.
- Foam nitrile coating, "second skin" effect, on palm and fingers.
- CUTXP 15 gauge knitting for a unique comfort experience.
- Good grip in oily conditions.
- Resistant to contact heat.
- Maximal cut protection.
- · Category II glove, protection against mechanical risks only.

Material: high performance polyethylene fibers (HPPE), tungsten, polyester and spandex.

X/4

1/4

X/4

X/4 X/4

X/4

Coating: Black nitrile foam.

Length: 22 to 27 cm depending on size.

Applications

- Handling of heavy greasy or oily sharp objects
- Assembly workstations
- Waste collection
- Automobile industry
- Glass and metal industries
- · Metal-working industry

Standards - Performance levels

Resistance to flammability

Small splashes of molten metal

Large splashes of molten metal

"X" means that the test has not been performed

Contact heat

Radiant heat

Convective heat

EN388: 2016 +A1:2018

EN407: 2020

X.1.X.X.X.X

ADITASION resistance	4/4
Cut resistance (coup test)	X/5
Tear resistance	4/4
Puncture resistance	2/4
Cut resistance (TDM test)	F
Contact heat resistance	1/4











EN ISO 21420: 2020





Sizes / SKU numbers

6	68 041 775
7	68 041 783
8	68 041 791
9	68 041 805
10	68 041 813
11	68 041 821

Packaging

- Individual bag (one pair)
- Polybag of 5 pairs
- Box of 50 pairs

